

Cut woven carpet - CWC78N

Specification according to EN 1307

Dot Contract

DESIGN	Cut-Woven 2200	
Product Type	Rolls	
Collection	...	
Style Number	...	
Construction(Manufacturing procedure)	DIN ISO 2424	woven
Structure of use surface	ISO 2424	Cut pile, single level
Pile Material	ISO 2424	100% POLYESTER
Dye Method(Colouring)	multicolored patterned	
Treatment	DOT Soil Protection	
Backing Material	Polyester, Latex	
Primary Backing	ISO 2424	...
Secondary Backing	ISO 2424	non-woven textile heavy backing *
Width	ISO 3018	max. 400 mm
Pile Height	ISO 1766	4.8 mm
Total Height	ISO 1765	6.9 mm
Pile Weight	ISO 2424	2200 g/m ²
Total Weight	ISO 8543	2950 g/m ²
Pitch	700 ends per Meter	
Rows	1300 M	
Gauge	...	
Stitches Per Inch	...	
Average Density	1.67 g/cm ³	
Fiber Type	polyester	
PERFORMANCE		
Basic requirements	fulfilled	
Body voltage, walking test	± 0,1 kV	
Classification according to EN 14041	antistatic	
Vertical resistance	ISO 10965	2,2 x 10 ⁹ Ω
Horizontal resistance	ISO 10965	2,6 x 10 ¹¹ Ω
Classification for use	EN 1307	Class 33-Heavy commercial use
Luxury rating class(Comfort Class EN 1307)	EN 1307	LC2
Flammability	EN 13501-1	Cfl - s1
Flame Spread	EN ISO 11925-2	≤ 150 mm
Critical Radiant Flux	EN ISO 9239-1	7.5 Kw/m ²
Smoke Density	EN ISO 9239-1	192
Colour Fastness To Rubbing	ISO 105-X12	≥ 4-5
Suitability for Stair	EN 1963	Yes
Suitable for heated floor	ISO 8302	Yes
RECOMMENDED INSTALLATION METHOD	direct glue	

* On Demand

